

# HistoBath



📍 Municipiul Botoșani, Aleea  
MAXIM GORKI, Nr .19 scara B  
Ap.3, judet Botoșani , Romania



[www.pregamedical.com](http://www.pregamedical.com)





## **General Features:**

- Working temperature adjustable from ambient temperature +5°C up to 80°C
- External body made from stainless steel ASTM 304
- Deep black surface interior bath with white illumination to facilitate clear identification of premium sections.
- PID controller with safety feature visual and acoustic alarm system
- Thermostatic bath designed for collecting and drying histological sample sections
- Ensures water temperature stability to facilitate proper handling of sections

## **Technical features**

- Working temperature for basin adjustment from +5°C above ambient temperature up to 80°C
- PID controller with safety features including visual and acoustic alarm systems for malfunction or over-temperature conditions
- Slide dryer plate temperature adjustable from ambient temperature +5°C up to 110°C using mechanical thermostat

## **Structural features :**

- External body made from stainless steel ASTM304
- Interior bath features deep black surface
- LED daylight illumination enhance visibility for premium section collection identification
- Slide Dryer Plate located on the back side, carries up to 20 slides

## **Dimensional features**

- Dimensions histo-bath (WxDxH): 345x400x130 mm
- Internal basin dimensions (WxDxH): 250x200x50 mm
- Slide-dryer plate dimensions (WxD): 325x100 mm
- Capacity: 2 Liter
- Net Weight: 5Kg
- Shipping Weight: 6Kg

## **Electrical connections**

- Power Supply : 220 to 240 V- 50/60 Hz
- Power Consumption : 450 VA
- Fuse : 4 A